


ENTRANCE PANEL

AA-07FBC


EAN: 5060514914489 (SILVER)

AA-07FBC is a multi apartment panel that made it possible to make calls from this device both to two-wire digital intercom systems of the Laskomex type and to IP intercoms.

BAS-IP hybrid panels support simultaneous operation with 3 systems: directly with the BAS-IP digital IP system, with VoIP telephony systems (operating via SIP) and the Laskomex digital two-wire system (RAIKMANN, RAINMAN, MARSHAL, KEIMAN, FILMAN, XVOICE).



SILVER



Main features

- Panel type: Multi-apartment.
- Display: 4.3" TFT, color with backlight.
- Keypad: Backlight mechanical buttons.
- Camera: 1/3".
- Resolution: 2 Mp.
- Camera angle: 110° (horizontal).
- Output video: Full HD (1920 × 1080), H.264 Main Profile.
- Night backlight: 6 LEDs.
- Light sensitivity: 0,01 LuX.
- Protection class: IP65.
- IK-Code: IK07.
- Working temperature: -40 — +65 °C.
- Power consumption: 6,5 W, in standby — 3,6 W.
- Power supply: +12 V DC.
- Body: Aluminum.
- Colors: Silver.
- Dimensions for installation: 141 × 351 × 60 mm.
- Size of the panel: 155 × 375 × 55 mm.
- Installation: Flush, surface with BR-AA7 bracket.

Functionality

- **Interface:** Multi-language graphical and WEB interface.
- **Lock opening:**
 - By means of a monitor
 - Face Recognition Identification
 - By QR code
 - By guest link
 - By Pin
 - By access card
 - By license plates
 - The BAS-IP Intercom app
 - The BAS-IP Link app
 - The BAS-IP UKEY app
 - From API
- **Access control integration:** WIEGAND-26+ output
- **Shortcut buttons:** Concierge button.
- **Number of call melodies:** 4 polyphonic melodies, ability to customize melodies for different actions.
- **Authentication:** Separate password for settings, WEB – interface and RTSP stream.
- **Talking mode:** Full duplex.
- **Additionally:**
 - Software Link support
 - SIP P2P
 - Built-in relay
 - Proximity sensor
 - Open API